
## **ZANOTTI SLIDE IN Refrigeration System**









Air exhaust



Digital Controller with easy to use interface, programmable according to system requirements Main functions:


- · Adjustment of thermostat differential
- Entering work setting
- Automatic or manual defrost
- Evaporator fans start delay
- · Pause after defrost to drain condensation water
- Sensor breakdown alarm
- Turning cold room light on
- Protection on number of pressure switch cut-ins.

## **Features:**

- · No drainage required unit incorporates condensate vaporisation system\*
- · Reduced electrical supply required due to hot gas defrost
- · Coldroom bulkhead light and prewired connection supplied with each unit
- $\boldsymbol{\cdot}$  Vertical condenser discharge lending the unit to ceiling cavity hot air disposal
- Digital controller incorporating anti short cycle timer and defrost termination
- $\cdot$  Both medium and low temperature units rated to 45° C ambient
- · R404A refrigerant used in all systems
- $\boldsymbol{\cdot}$  Three pin plug fitted to all units
- Prewired for door sensor (and door heater on low temperature models.)
- \* Drainage may be required for certain applications/areas- POA

WARRANTY 1 yr PARTS	CHILLER Medium Temperature Range -5 to +10°C Room Temp							FREEZER Low Temperature Range -5 to -25°C Room Temp.				
	MGM106	MGM110	MGM211	MGM213	MGM315	MGM320	BGM218	BGM220	BGM320	BGM330		
Bromic Part Number	3835201	3835203	3835204	3835205	3835206	3835207	3835254	3835251	3835252	3835253		
Capacity (Watts)	1100W	1500W	1960W	2600W	3440W	3850W	1210W	1660W	2190W	2650W		
Temperature range (°C)	-5 to +10°	-5 to +10°	-5 to +10°	-5 to +10°	-5 to +10°	-5 to +10°	-5 to -25°	-5 to -25°	-5 to -25°	-5 to -25°		
Max ambient temp (°C)	45°C	45°C	45°C	45°C	45°C	45°C	45°C	45°C	45°C	45°C		
Run/Full-Load Amps (Amps)	5/8.3A	5.6/11.2A	6.9/12.4A	9.3/18.0A	8.5/16.1A	11.5/17.1A	5.9/11.7A	7.5/20.9A	9.9/25.1A	9.9/25.1A		
External Dimensions	See below	See below	See below	See below	See below	See below	See below	See below	See below	See below		
Defrost Type	Hot gas	Hot gas	Hot gas	Hot gas	Hot gas	Hot gas	Hot gas	Hot gas	Hot gas	Hot gas		
Type of control	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic	Electronic		
Temperature display	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital	Digital		
Interior light	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		
Gross weight (kg)	56kg	64kg	80kg	80kg	98kg	100kg	80kg	80kg	105kg	105kg		
Refrigerant	R404a	R404a	R404a	R404a	R404a	R404a	R404a	R404a	R404a	R404a		
Single Phase required	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes	Yes		

## See page 54/55 for matching "Refrigeration Unit to Coolroom Size"



Model/mm	Α	В	С	D	Е	F
MGM106/110	735	790	400	280	510	368
MGM211/211ASP/213 BGM218/220	830	790	620	280	510	585
MGM315/320 BGM320/330	830	862	620	350	512	585